

FLARE SHIELD BLOCK WALL RELOCATION

GENERAL REQUIREMENTS DOCUMENT

8/25/2015

1. Partition NCSX and FLARE within CS High Bay with no direct access to each space.
2. Existing shield block wall directly in front of roll up doors to remain and act as a boundary line between NCSX and FLARE.
3. Remove existing north shield block wall and portion of existing west shield block wall.
4. Relocate pieces from north and/or west shield block wall to infill existing opening and partition each space.
5. Relocate remaining shield block pieces to TFTR test cell for storage.
6. Attach seismic bracing to relocated shield block infill wall.
7. Shine is not a requirement.
8. Space planning within NCSX space is not a requirement.

Erik D. Perry

Digitally signed by Erik D. Perry
DN: cn=Erik D. Perry, o, ou,
email=eperry@pppl.gov, c=US
Date: 2015.09.03 11:43:55 -04'00'

Erik Perry

Date

**Michael
Kalish**

Digitally signed by Michael Kalish
DN: cn=Michael Kalish, o=PPPL,
ou=Engineering,
email=mkalish@pppl.gov, c=US
Date: 2015.09.03 08:05:34 -04'00'

Michael Kalish

Date

**Martin
Donohue**

Digitally signed by Martin Donohue
DN: cn=Martin Donohue, o=PPPL,
ou=Facilities,
email=mtonohue@pppl.gov, c=US
Date: 2015.09.02 16:13:40 -04'00'

Martin Donohue

Date

**David P.
Pryor**

Digitally signed by David P. Pryor
DN: cn=David P. Pryor, o=PPPL,
ou=Facilities,
email=dpryor@pppl.gov, c=US
Date: 2015.08.25 15:10:59 -04'00'

David Pryor

Date